



SPECIFICATIONS **CDMA8814R2G2W**

OUTLINES DIMENSIONS




PIN1

COL	1	2	3	4	5	6	7	8
ROW	○	○	○	○	○	○	○	○
2	○	○	○	○	○	○	○	○
3	○	○	○	○	○	○	○	○
4	○	○	○	○	○	○	○	○
5	○	○	○	○	○	○	○	○
6	○	○	○	○	○	○	○	○
7	○	○	○	○	○	○	○	○
8	○	○	○	○	○	○	○	○



10.3

2.54*11=27.94



28.2

0.51

Notes:

1. All Dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25\text{mm}$ (0.01") unless otherwise noted.
3. Specifications are subject to change without notice.

Part Number	Chip Material	Color of Emission	Lens Type	Description
CDMA8814R2G2W	InGaAlP	Red	White Segment/ Grey Face	Row Anode
	InGaAlP	Green		



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

ABSOLUTE MAXIMUM RATINGS - RED (InGaAlP)
(TA=25°C)

Parameter	Symbol	Max Rating	Unit
Power Dissipation	PD	50	mW
Pulse Forward Current	IFP	80	mA
Continuous Forward Current	IF	20	mA
Reverse Voltage	VR	5	V
Operating Temperature Range	TOPR	-25~+85	°C
Storage Temperature Range	TSTG	-25~+85	°C
IFP = Pulse Width ≤ 10 ms, Duty Ratio ≤1/10. Soldering Condition: 260 °C/ 3sec			

OPTICAL-ELECTRICAL CHARACTERISTICS - RED (InGaAlP)
(TA=25°C)

Parameter	Symbol	Test Condition	Value			Unit
			Min	Typ	Max	
Luminous Intensity	IV	IF = 10mA	80	100	-	mcd
Forward Voltage	VF	IF = 10mA	-	2.0	2.4	V
Reverse Leakage Current	IR	VR = 5V	-	-	50	µA
Peak Wavelength	λP	IF = 10mA	629	-	635	nm
Dominant Wavelength	λD	IF = 10mA	-	630	-	nm
Spectral Radiation Bandwidth	Δλ	IF = 10mA	-	20	-	nm



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

ABSOLUTE MAXIMUM RATINGS - GREEN (InGaAlP)
(TA=25°C)

Parameter	Symbol	Max Rating	Unit
Power Dissipation	PD	50	mW
Pulse Forward Current	IFP	80	mA
Continuous Forward Current	IF	20	mA
Reverse Voltage	VR	5	V
Operating Temperature Range	TOPR	-20~+85	°C
Storage Temperature Range	TSTG	-20~+100	°C
IFP = Pulse Width ≤ 10 ms, Duty Ratio ≤ 1/10. Soldering Condition: 260 °C/ 5sec			


OPTICAL-ELECTRICAL CHARACTERISTICS - GREEN (InGaAlP)
(TA=25°C)

Parameter	Symbol	Test Condition	Value			Unit
			Min	Typ	Max	
Luminous Intensity	IV	IF = 10mA	30	40	-	mcd
Forward Voltage	VF	IF = 10mA	-	2.0	2.4	V
Reverse Leakage Current	IR	VR = 5V	-	-	50	µA
Peak Wavelength	λP	IF = 10mA	568	-	572	nm
Dominant Wavelength	λD	IF = 10mA	-	573	-	nm
Spectral Radiation Bandwidth	Δλ	IF = 10mA	-	20	-	nm



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com


INTERNAL CIRCUIT DIAGRAM




ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

OPTICAL CHARACTERISTIC CURVES - RED


Forward Current VS. Ambient Temperature




Relative Intensity VS. Ambient Temperature



Forward Current VS. Forward Voltage




Forward Voltage VS. Ambient Temperature



Luminous Spectrum ($T_a=25^\circ\text{C}$)
RADIANCE


SPECTRAL




ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

OPTICAL CHARACTERISTIC CURVES - GREEN


Forward Current V.S. Ambient Temperature




Relative Intensity V.S. Ambient Temperature




Forward Current V.S. Forward Voltage




Forward Voltage V.S. Ambient Temperature



Luminous Spectrum (Ta=25°C)
RADIANCE



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

RECOMMENDED SOLDERING PROFILE
● RECOMMEND SOLDERING PROFILE

● SOLDERING IRON

Basic spec is ≤ 4 sec when 260°C. If temperature is higher, time should be shorter (+10°C → 1 sec). Power dissipation of Iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C.

● REWORK

Customer must finish rework within ≤ 4 sec under 245°C.



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com