


SPECIFICATIONS **CTD5959GT2WB**

OUTLINES DIMENSIONS



The technical drawings show the following dimensions:

- Top View:** Overall width 15.00mm, overall height 15.00mm. An inner square has a side length of 8.00mm. A yellow shaded area labeled "Touch PAD" is centered within this square. The distance from the left edge to the center of the touch pad is 5.00 ± 0.5mm. The distance from the center of the touch pad to the right edge is 6.80mm.
- Bottom View:** Shows a central "P / N ." region. The diameter of the central region is 0.50mm. The distance from the center to the edge of the bottom pad is 5.08mm. The total width of the bottom pad is 5.75mm. The distance from the center to the edge of the side pad is 1.87mm. A film layer is indicated as "FILM, T=0.2mm".

Notes:

1. All Dimensions are in millimeters (inches).
2. Tolerance is ± 0.25mm (0.01") unless otherwise noted.
3. Specifications are subject to change without notice.

Part Number	Chip Material	Color of Emission	Lens Type	Description
CTD5959GT2WB	InGaN	Green	White	Touch Display



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

ABSOLUTE MAXIMUM RATINGS
(TA=25°C)

Parameter	Symbol	Max Rating	Unit
Power Dissipation	PD	120	mW
Continuous Forward Current (Per Dice)	IF	30	mA
Peak Current (Per Dice)	IFP	100	mA
Reverse Voltage (Per Dice)	VR	5	V
Operating Temperature Range	TOPR	-25~+85	°C
Storage Temperature Range	TSTG	-25~+85	°C
Hand Soldering Condition: 360 °C/ 3sec			


OPTICAL-ELECTRICAL CHARACTERISTICS
(TA=25°C)

Parameter	Symbol	Test Condition	Value			Unit
			Min	Typ	Max	
Luminous Intensity	IV	IF = 20mA	-	90	-	mcd
Forward Voltage	VF	IF = 20mA	-	3.2	4.0	V
Reverse Leakage Current	IR	VR = 5V	-	-	10	µA
Dominant Wavelength	λD	IF = 20mA	-	525	-	nm
Spectral Radiation Bandwidth	Δλ	IF = 20mA	-	30	-	nm




ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

INTERNAL CIRCUIT DIAGRAMS



TYPICAL APPLICATION CIRCUITS



Internal Components are not customer accessible



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

OPTICAL CHARACTERISTIC CURVES




Fig.1 RELATIVE INTENSITY VS. FORWARD CURRENT




Fig.2 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.3 RELATIVE INTENSITY VS. LEAD TEMPERATURE
(PULSED 20 mA; 300us PULSE, 10ms PERIOD)




Fig.4 PEAK FORWARD VOLTAGE VS. FORWARD (100us TEST PULSE, 1% DUTY CYCLE)




Fig.5 RELATIVE INTENSITY VS. WAVELENGTH





Fig.6 MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com

SOLDERING CHARACTERISTICS

NOTES

1. Recommend pre-heat temperature of 105°C or less (as measured with a thermocouple attached to the LED pins) prior to immersion in the solder wave with a maximum solder bath temperature of 260°C
2. Peak wave soldering temperature between 245°C ~ 225°C for 3 sec (5 sec max)
3. No more than one wave soldering pass

SOLDERING IRON

- Basic spec is ≤ 4 sec when 260°C. If temperature is higher, time should be shorter (+10°C → 1 sec). Power dissipation of Iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C

REWORK

1. Customer must finish rework within 3 sec under 350°C
2. The head of soldering iron cannot touch copper foil



ChromeLED Corp. reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.chromeled.com